

## □ Cleaning of semipermeable membranes in filtration units

L20 ANSWER 9 OF 121 HCA COPYRIGHT 2002 ACS FAMILY 4  
AN 87:156960 HCA  
IN Sano, Takezo; Shimomura, Takatoshi; Sasaki, Masao  
PA Sumitomo Chemical Co., Ltd., Japan  
SO Japan. Kokai, 3 pp.  
CODEN: JKXXAF  
DT Patent  
LA Japanese  
FAN.CNT 1

|    | PATENT NO.  | KIND | DATE     | APPLICATION NO. | DATE     |
|----|---|------|----------|-----------------|----------|
| PI | JP 52058078   | A2   | 19770513 | JP 1975-134314  | 19751108 |
| AB | A contaminated semipermeable <b>membrane</b> (parallel flow) filter unit (reverse osmosis or ultrafiltration) is regularly flushed in a short period with a high pressure gas to contact the <b>membrane</b> with a <b>gas-liq. mixt.</b> , thus <b>removing</b> the <b>contaminated</b> layer. The method is used for any shape of unit. Thus, a tubular cellulose acetate [9004-35-7] <b>membrane</b> filter unit for tap water was used 200 h, then flushed 3 min with N at 35 kg/cm <sup>2</sup> . The salt removal was 94.8% initially, 89.7% after 200 h use, and 94.7% after cleaning. |      |          |                 |          |